



## OBROČNA TESNILA LINK-SEAL Tehnični podatki

Notranji fi izvrtane luknje	Zunanji premer vstavljene cevi		Izbrano tesnilo	
	od	do	število elementov tesnila	tip
50	9	18	3	LU2
	17	24	4	LU1
80	39	42	5	LU2
	43	48	6	LU2
100	47	54	7	LU1
	38	50	5	LU4
	49	60	6	LU3
125	59	67	7	LU2
	67	74	9	LU1
	48	63	5	LU5
	62	74	6	LU4
	74	85	8	LU3
150	84	86	9	LU2
	87	93	10	LU2
	92	95	11	LU1
	96	99	12	LU1
	57	74	5	LU6
	73	82	6	LU5
	83	88	7	LU5
200	87	100	8	LU4
	99	110	10	LU3
	109	118	12	LU2
	117	124	14	LU1
	88	108	6	LU7
	107	124	7	LU6
250	124	138	9	LU5
	137	150	11	LU4
	144	160	14	LU3
	159	167	16	LU3
	117	138	6	LU8
	137	141	7	LU7
	142	158	8	LU7
	157	161	9	LU6
	162	174	10	LU6
	173	188	12	LU5
300	187	193	14	LU4
	194	200	15	LU4
	199	210	18	LU3
	143	168	7	LU9
	167	172	7	LU8
	173	188	8	LU8
	187	196	9	LU7
	197	208	10	LU7
	207	224	12	LU6
	223	238	15	LU5
400	237	250	18	LU4
	249	260	22	LU3

Notranji fi izvrtane luknje	Zunanji premer vstavljene cevi		Izbrano tesnilo	
	od	do	število elementov tesnila	tip
350	169	194	8	LU10
	193	213	8	LU9
400	214	218	9	LU9
	217	238	9	LU8
	237	250	11	LU7
	251	258	12	LU7
	257	274	14	LU6
	275	288	17	LU5
	287	300	21	LU4
	300	310	26	LU5
	194	217	8	LU11
	218	220	9	LU11
450	219	229	9	LU10
	230	244	10	LU10
	243	268	10	LU9
	267	288	11	LU8
	287	305	13	LU7
	306	308	14	LU7
	307	314	16	LU6
	315	324	17	LU6
	323	331	20	LU5
	332	338	21	LU5
500	337	349	24	LU4
	244	270	10	LU11
	269	294	11	LU10
	293	311	11	LU9
	312	318	12	LU9
	317	338	12	LU8
	337	358	15	LU7
	357	374	19	LU6
	373	388	23	LU5
	387	390	27	LU4
500	391	400	28	LU4
	294	320	11	LU11
	319	328	12	LU10
	329	344	13	LU10
	343	368	13	LU9
	367	388	14	LU8
	387	408	17	LU7
	407	424	21	LU6
	423	438	26	LU5

**Tip Z:** EPDM elastomer, temp. razpon -30°C do +100°C, pocinkani vijaki

**Tip A2:** korozijsko odporen, EPDM elastomer, vijaki iz nerjavečega jekla

**Tip KTW:** EPDM elastomer atestiran za pitno vodo, vijaki iz nerjav. jekla