

Distantni prsteni tip AKM – tehnički list

Vanjski Ø cijevi [mm]	Br. elemenata u prstenu		Vijci od nehrđajućeg čelika	Širina distancera	Visina distancera
	AKM 1	AKM 1,5	Br. / dimenzija	L [mm]	H [mm]
od - do	AKM 1	AKM 1,5	Br. / dimenzija	L [mm]	H [mm]
400-430	4		8 / M8x70	160	25
450-480	3	1	8 / M8x70		
500-538	5		10 / M8x70		
550-585	4	1	10 / M8x70		
600-628		4	8 / M8x70		36
629-649	6		12 / M8x70		
650-680	2	3	10 / M8x70		
680-699	5	1	12 / M8x70		
700-732	1	4	10 / M8x70		50
732-750	7		14 / M8x70		
751-780		5	10 / M8x70		
780-799	6	1	14 / M8x70		
800-835	2	4	12 / M8x70		75
835-850	8		16 / M8x70		
851-880	1	5	12 / M8x70		
880-900	7	1	16 / M8x70		
901-951		6	12 / M8x70	100	
952-1000	2	5	14 / M8x70		
1001-1050	1	6	14 / M8x70		
1051-1100		7	14 / M8x70		
1101-1150	2	6	16 / M8x70	125	
1151-1200	1	7	16 / M8x70		
1201-1249		8	14 / M8x70		

Statička nosivost distancera:

- visina 25, 36, 50 i 75 mm: 2000 kg/prsten
- visina 100 i 125 mm: 1000 kg/prsten

Materijal:

- distancer: polypropylen, crni
- vijci i matice: nehrđajući čelik



Element AKM 1



Element AKM 1,5